Tektronix[®]

4 GHz Active Probe P7240 Datasheet



The P7240 4 GHz, 5X active FET probe provides truer signal reproduction and fidelity for high-frequency measurements. The probe has low input capacitance and high input resistance to minimize circuit loading over a wide bandwidth range.

Features and benefits

- <120 ps Rise Time (Guaranteed)
- 4 GHz Bandwidth
- <1 pF input capacitance
- Small form factor probe head
- Direct access to SMDs
- Supports MSO/DPO/DSA70000 series oscilloscopes
- TekConnect[™] Interface

Applications

- High-speed digital systems design
- Component design/characterization
- Signal integrity, jitter, and timing analysis
- · Mechanical engineering and test
- Measures 3.0 V logic, InfiniBand, PCI Express, DDR, Rambus Data Lines, Gigabit Ethernet

Performance you can count on

Selecting the right probe for your application is key to attaining the best signal fidelity in your measurements. Active probes provide truer signal reproduction and fidelity for high-frequency measurements.

The small profile and low-mass head make probing dense circuitry by hand fast and easy.

Depend on Tektronix to provide you with performance you can count on. In addition to industry-leading service and support, this probe comes backed by a one-year warranty.

The accessory tips and adapters included with the P7240 probe enable it to be used on a wide variety of circuits to meet your probing needs.



TekConnect[™] Interface

The P7240 with TekConnect interface is a high-performance active probe with high bandwidth and low-capacitive loading to make it the probe of choice for demanding design applications, such as Rambus, DDR DRAM and AGP. This probe is also suited for applications in the communication industry, for measurements on Fibre Channel and Gigabit Ethernet. With the TekConnect interface, you can be assured that maximum signal integrity is maintained to meet present and future bandwidth needs.

Specifications

All specifications are guaranteed unless noted otherwise.

Warranted characteristics

Rise time	≤120 ps
Attenuation	5X

Typical characteristics

Bandwidth	4.0 GHz
DC resistance	20 kΩ
Input capacitance	<1 pF
Dynamic range	±2 V
Offset range	±5 V

Physical characteristics

Unit weight (probe only)	223 g (7.52 oz)
Cable length	1.3 m (50 in)

Environmental characteristics

Temperature	
Operating	0 °C to +40 °C (+32 °F to +104 °F)
Nonoperating	-55 °C to +75 °C (-67 °F to +167 °F)
Humidity	0 to 90% RH at +30 °C to +40 °C (+86 °F to +104 °F)
Altitude	
Operating	4572 m (15,000 ft)
Nonoperating	15,240 m (50,000 ft)

Ordering information

Models

P7240

4.0 GHz Active Probe

Standard accessories

Part number	Description	Quantity
006-3415-xx	Wrist strap	1
006-7164-xx	Accessory case	1
016-1315-xx	Color coding bands, 2 each of 5 colors	1
016-1772-xx	Pogo pin (set of 10)	1
016-1773-xx	Square pin socket (set of 10)	1
016-1774-xx	Adapter spring (set of 10)	1
016-1952-xx	Probe carrying case	1
071-0759-xx	User manual	1
131-5638-xx	Probe Tip (Set of 10)	1
131-6254-xx	SureToe [™] (set of 4)	1
196-3456-xx	Lead set consisting of: 3-in Ground lead (3) Y-Lead (2)	1
196-3482-xx	Customizable ground lead (set of 5)	1
206-0569-xx	SMT KlipChip [™] Adapter	2
-	Calibration data report	1

Recommended accessories

Part number	Description	Quantity
013-0309-xx	IC Grabber (set of 2)	1

Warranty

One-year warranty covering all parts and labor.

Options

Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R3	Repair Service 3 Years (including warranty)
Opt. R5	Repair Service 5 Years (including warranty)

Tektronix P7240 Probe Accessory Reorder List

Tektronix 131-6254-XX SureToe™ SET of 4	Tektronix 131-5638-XX PROBE TIP SET of 10	the opposite and the	Tektronix 016-1774-XX SPRING ADAPTER SET of 10
Tektronix 016-1772-XX POGO PIN GND SET of 10	Tektronix 016-173-XX SOCKET, SQ PIN SET of 10		O16-1315-XX COLOR MARKER BANDS SET SET of 1
196-3456-XX LEAD SET SET of 1 196-3482-XX CUSTOMIZABLE GROUND LEAD SET of 5			
206-0559-XX SMT KlipChip 2 EACH SET of 2			

CE Marking Not Applicable.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

Datasheet

ASEAN / Australasia (65) 6356 3900 Belgium 00800 2255 4835* Central East Europe and the Baltics +41 52 675 3777 Finland +41 52 675 3777 Hong Kong 400 820 5835 Japan 81 (3) 6714 3086 Middle East, Asia, and North Africa +41 52 675 3777 People's Republic of China 400 820 5835 Republic of Korea +822 6917 5084, 822 6917 5080 Spain 00800 2255 4835* Taiwan 886 (2) 2656 6688 Austria 00800 2255 4835* Brazii +55 (11) 3759 7627 Central Europe & Greece +41 52 675 3777 France 00800 2255 4835* India 000 800 650 1835 Luxembourg +41 52 675 3777 The Netherlands 00800 2255 4835* Poland +41 52 675 3777 Russia & CIS +7 (495) 6647564 Sweden 00800 2255 4835* United Kingdom & Ireland 00800 2255 4835* Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777 Canada 1 800 833 9200 Denmark +45 80 88 1401 Germany 00800 2255 4835* Italy 00800 2255 4835* Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90 Norway 800 16098 Portugal 80 08 12370 South Africa +41 52 675 3777 Switzerland 00800 2255 4835* USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright [©] Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

27 Jun 2017 51W-26152-6

ES)

www.tek.com

Tektronix[®]