

Agilent 33250A Function/Arbitrary Waveform Generator

Data Sheet



- 80 MHz sine and square wave outputs
- Sine, square, ramp, noise and other waveforms
- 50 MHz pulse waveforms with variable rise/fall times
- 12-bit, 200 MSa/s, 64K-point deep arbitrary waveform

Built-in Versatility

AM, FM and FSK capabilities make it easy to modulate waveforms with or without a separate source. Linear or logarithmic sweeps can be performed with a programmable frequency marker signal. Programmable burst count and gating allow you to further customize your signal.

For system applications, both GPIB and RS-232 interfaces are standard, and support full programmability using SCPI commands.

Color Graphical Display

The unique design of the 33250A combines a low-profile instrument with the benefits of a color graphical display. Now you can display multiple waveform parameters at the same time. The graphical interface also allows you to modify arbitrary waveforms quickly and easily.

Timebase Stability and Clock Reference

The 33250A TCXO timebase gives you frequency accuracy of 2 ppm for your most demanding applications. The external clock reference input/output lets you synchronize to an external 10 MHz clock, to another 33250A, or to an Agilent 33120A. Phase adjustments can be made from the front panel or via a computer interface, allowing precise phase calibration and adjustment.

Standard Waveforms

The Agilent Technologies 33250A Function/Arbitrary Waveform Generator uses direct digital-synthesis techniques to create a stable, accurate output on all waveforms, down to 1 μ Hz frequency resolution. The benefits are apparent in every signal you produce, from the sine wave frequency accuracy to the fast rise/fall times of square waves, to the ramp linearity.

Front-panel operation of the 33250A is straightforward and user friendly. The knob or numeric keypad can be used to adjust frequency, amplitude and offset. You can even enter voltage values directly in Vpp, Vrms, dBm, or high/low levels. Timing parameters can be entered in hertz (Hz) or seconds.

Custom Waveform Generation

Why settle for a basic function generator when you can get arbitrary waveforms at no extra cost? With the 33250A, you can generate arbitrary waveforms with 12-bit vertical resolution, 64K memory depth, and a sample rate of 200 MSa/s. You can also store up to four 64K-deep arbitrary waveforms in non-volatile memory with

user-defined names to help you find the right waveform when you need it most.

The included Agilent IntuiLink software allows you to easily create, edit, and download complex waveforms using the IntuiLink Arbitrary Waveform Editor. Or you can capture a waveform using IntuiLink oscilloscope or DMM and send it to the 33250A for output. For programmers, ActiveX components can be used to control the instrument using SCPI commands. IntuiLink provides the tools to easily create, download, and manage waveforms for your 33250A. To find out more about IntuiLink, visit www.agilent.com/find/intuilink.

Pulse Generation

The 33250A can generate simple pulses up to 50 MHz. With variable edge time, pulse width and voltage level, the 33250A is ideally suited to a wide variety of pulse applications.



Agilent Technologies

WAVEFORMS

| | |
|----------------------|---|
| Standard | sine, square, pulse, ramp, noise, sin(x)/x, exponential rise, exponential fall, cardiac, DC volts |
| Arbitrary | |
| Waveform length | 1 to 64K points |
| Amplitude resolution | 12 bits (including sign) |
| Repetition rate | 1 μ Hz to 25 MHz |
| Sample rate | 200 MSa/s |
| Filter bandwidth | 50 MHz |
| Non-vol. memory | Four (4) 64K waveforms |

FREQUENCY CHARACTERISTICS

| | |
|-------------------|---|
| Sine | 1 μ Hz to 80 MHz |
| Square | 1 μ Hz to 80 MHz |
| Pulse | 500 μ Hz to 50 MHz |
| Arb | 1 μ Hz to 25 MHz |
| Ramp | 1 μ Hz to 1 MHz |
| White noise | 50 MHz bandwidth |
| Resolution | 1 μ Hz; except pulse, 5 digits |
| Accuracy (1 year) | 2 ppm, 18°C to 28°C 3 ppm, 0°C to 55°C |

SINEWAVE SPECTRAL PURITY

Harmonic distortion

| | ≤ 3 Vpp ¹ | > 3 Vpp |
|-------------|---------------------------|-----------|
| DC to 1 MHz | -60 dBc | -55 dBc |
| 1 to 5 MHz | -57 dBc | -45 dBc |
| 5 to 80 MHz | -37 dBc | -30 dBc |

Total harmonic distortion

| | |
|--------------|-----------------------|
| DC to 20 kHz | $< 0.2\% + 0.1$ mVrms |
|--------------|-----------------------|

Spurious (non-harmonic)²

| | |
|--------------|------------------------|
| DC to 1 MHz | -60 dBc |
| 1 to 20 MHz | -50 dBc |
| 20 to 80 MHz | -50 dBc + 6 dBc/octave |

Phase noise (30 kHz band)

| | |
|--------|-----------------------|
| 10 MHz | < -65 dBc (typical) |
| 80 MHz | < -47 dBc (typical) |

SIGNAL CHARACTERISTICS

Squarewave

| | |
|----------------|---------------------|
| Rise/Fall time | < 8 ns |
| Overshoot | $< 5\%$ |
| Asymmetry | 1% of period + 1 ns |
| Jitter (rms) | |
| < 2 MHz | 0.01% + 525 ps |
| ≥ 2 MHz | 0.1% + 75 ps |
| Duty cycle | |
| ≤ 25 MHz | 20.0% to 80.0% |
| 25 to 50 MHz | 40.0% to 60.0% |
| 50 to 80 MHz | 50.0% fixed |

Pulse

| | |
|--------------------|----------------------|
| Period | 20.00 ns to 2000.0 s |
| Pulse width | 8.0 ns to 1999.9 s |
| Variable edge time | 5.00 ns to 1.00 ms |
| Overshoot | $< 5\%$ |
| Jitter (rms) | 100 ppm + 50 ps |

Ramp

| | |
|-----------|--------------------------|
| Linearity | $< 0.1\%$ of peak output |
| Symmetry | 0.0% - 100.0% |

Arb

| | |
|----------------|----------------------------------|
| Min. edge time | < 10 ns |
| Linearity | $< 0.1\%$ of peak output |
| Settling time | < 50 ns to 0.5% of final value |
| Jitter (rms) | 30 ppm + 2.5 ns |

OUTPUT CHARACTERISTICS

| | |
|--|--|
| Amplitude (into 50 Ω) | 10 mVpp to 10 Vpp |
| Accuracy (at 1 kHz, > 10 mVpp, Autorange) | $\pm 1\%$ of setting ± 1 mVpp |
| Flatness (sinewave relative to 1 kHz, Autorange) | |
| < 10 MHz | $\pm 1\%$ (0.1 dB) |
| 10 to 50 MHz | $\pm 2\%$ (0.2 dB) |
| 50 to 80 MHz | $\pm 5\%$ (0.4 dB) |
| Units | Vpp, Vrms, dBm, high and low level |
| Resolution | 0.1 mV or 4 digits |
| Offset (into 50 Ω) | ± 5 Vpk ac + dc |
| Accuracy | 1% of setting + 2 mV + 0.5% of amplitude |

Waveform Output

| | |
|------------|--|
| Impedance | 50 Ω typical (fixed) > 10 M Ω (output disabled) |
| Isolation | 42 Vpk maximum to earth |
| Protection | short-circuit protected; overload automatically disables main output |

MODULATION

AM

| | |
|-------------------|------------------------------------|
| Carrier waveforms | sine, square, ramp, and arb |
| Mod. waveforms | sine, square, ramp, noise, and arb |
| Mod. frequency | 2 MHz to 20 kHz |
| Depth | 0.0% to 120.0% |
| Source | internal/external |

FM

| | |
|-------------------|------------------------------------|
| Carrier waveforms | sine, square, ramp, and arb |
| Mod. waveforms | sine, square, ramp, noise, and arb |
| Mod. frequency | 2 MHz to 20 kHz |
| Peak deviation | DC to 80 MHz |
| Source | internal/external |

FSK

| | |
|-------------------|-----------------------------|
| Carrier waveforms | sine, square, ramp, and arb |
| Mod. waveform | 50% duty cycle square |
| Internal rate | 2 MHz to 1 MHz |
| Frequency range | 1 μ Hz to 80 MHz |
| Source | internal/external |

External Modulation Input

| | |
|-----------------|----------------------|
| Voltage range | ± 5 V full scale |
| Input impedance | 10 k Ω |
| Frequency | DC to 20 kHz |

BURST

| | |
|-------------------|--|
| Waveforms | sine, square, ramp, pulse, arb, and noise |
| Frequency | 1 μ Hz to 80 MHz ³ |
| Burst count | 1 to 1,000,000 cycles or infinite |
| Start/Stop phase | -360.0° to +360.0° |
| Internal period | 1 ms to 500 s |
| Gate source | external trigger |
| Trigger source | single manual trigger, internal, external trig |
| Trigger delay | |
| N-cycle, infinite | 0.0 ns to 85.000 sec |

SWEEP

| | |
|----------------|--|
| Waveforms | sine, square, ramp, and arb |
| Type | linear and logarithmic |
| Direction | up or down |
| Start F/Stop F | 100 μ Hz to 80 MHz |
| Sweep time | 1 ms to 500 s |
| Trigger | single manual trigger, internal, external trig |
| Marker | falling edge of sync signal (programmable) |

SYSTEM CHARACTERISTICS

Configuration Times (typical)

| | |
|-------------------|-------------------------|
| Function change | |
| Standard | 100 ms |
| Pulse | 660 ms |
| Built-in arb | 220 ms |
| Frequency change | 20 ms |
| Amplitude change | 50 ms |
| Offset change | 50 ms |
| Select user arb | < 900 ms for < 16K pts. |
| Modulation change | < 200 ms |

Arb Download Times GPIB/RS-232 (115Kbps)

| Arb Length | Binary | ASCII Integer | ASCII Real |
|------------|---------|---------------|------------|
| 64K points | 48 sec | 112 sec | 186 sec |
| 16K points | 12 sec | 28 sec | 44 sec |
| 8K points | 6 sec | 14 sec | 22 sec |
| 4K points | 3 sec | 7 sec | 11 sec |
| 2K points | 1.5 sec | 3.5 sec | 5.5 sec |

TRIGGER CHARACTERISTICS

Trigger input

| | |
|-----------------|-------------------------------|
| Input level | TTL compatible |
| Slope | rising or falling, selectable |
| Pulse width | > 100 ns |
| Input impedance | 10 k Ω , DC coupled |
| Latency | |
| Burst | < 100 ns (typical) |
| Sweep | < 10 μ s (typical) |
| Jitter (rms) | |
| Burst | 1 ns; except pulse, 300 ps |
| Sweep | 2.5 μ s |

Trigger output

| | |
|--------------|---------------------------------|
| Level | TTL compatible into 50 Ω |
| Pulse width | > 450 ns |
| Maximum rate | 1 MHz |
| Fanout | \leq 4 Agilent 33250A's |

CLOCK REFERENCE

Phase Offset

| | |
|------------|----------------|
| Range | -360° to +360° |
| Resolution | 0.001° |

External Reference Input

| | |
|------------|----------------------------------|
| Lock range | 10 MHz \pm 35 kHz |
| Level | 100 mVpp to 5 Vpp |
| Impedance | 1 k Ω nominal, ac coupled |
| Lock time | < 2 s |

Internal Reference Output

| | |
|-----------|---------------------------------|
| Frequency | 10 MHz |
| Level | 632 mVpp (0 dbm), nominal |
| Impedance | 50 Ω nominal, ac coupled |

SYNC OUTPUT

| | |
|-----------|------------------------------------|
| Level | TTL compatible into > 1 k Ω |
| Impedance | 50 Ω nominal |

GENERAL

| | |
|----------------------|---|
| Power supply | 100-240 V, 50-60 Hz 100-127 V, 50-400 Hz |
| Power consumption | 140 VA |
| Operating temp. | 0°C to 55°C |
| Storage temp. | -30°C to 70°C |
| Stored states | 4 named user configurations |
| Power on state | default or last |
| Interface | IEEE-488 and RS-232 std. |
| Language | SCPI-1997, IEEE-488.2 |
| Dimensions (WxHxD) | |
| Bench top | 254 x 104 x 374 mm |
| Rackmount | 213 x 89 x 348 mm |
| Weight | 4.6 kg |
| Safety designed to | EN61010-1, CSA1010.1, UL-311-1 |
| EMC tested to | IEC-61326-1 IEC-61000-4-3 criteria B IEC-61000-4-6 criteria B |
| Vibration and shock | MIL-T-28800E, Type III, Class 5 |
| Acoustic noise | 40 dBA |
| Warm-up time | 1 hour |
| Calibration interval | 1 year |
| Warranty | 1 year |

¹ Harmonic distortion at low amplitudes is limited by a -70 dBm floor

² Spurious noise at low amplitudes is limited by a -75 dBm floor

³ Sine and square waveforms above 25 MHz only with infinite burst count

Ordering Information

Agilent 33250A

Function/Arbitrary
Waveform Generator

Accessories Included

Operating manual, service manual, quick reference guide, IntuiLink connectivity software, test data, RS-232 cable, and power cord.

Options

Opt. 1CM Rackmount kit*
(Agilent 34190A)

Accessories

10100C 50Ω feedthru
11094B 75Ω feedthru
11095A 600Ω feedthru
34131A Carrying case
34161A Accessory pouch
34190A Rackmount kit*
34811A BenchLink Arb software

*For racking two 33250As side-by-side, order the following items:

Lock-link kit (p/n 5061-9694)
Flange kit (p/n 5063-9212)

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty.

Support is available for at least five years beyond the production life of the product. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you use Agilent equipment, we can verify that it works properly, help with product operation, and provide basic measurement assistance for the use of specified capabilities, at no extra cost upon request. Many self-help tools are available.

Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and on-site education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

For more information on Agilent Technologies products, applications or services, please contact your local office.

The complete listing is available at:
www.agilent.com/find/contactus

Phone or Fax United States:

(tel) 1 800 829 4444
(fax) 1 800 829 4433

Canada:

(tel) 1 877 894 4414
(fax) (905) 282 6495

China:

(tel) 800 810 0189
(fax) 800 820 2816

Japan:

(tel) (81) 426 56 7832
(fax) (81) 426 56 7840

Korea:

(tel) (080) 769 0800
(fax) (080) 769 0900

Latin America:

Headquarters:
(tel) (305) 269 7500

Taiwan:

(tel) 0800 047 866
(fax) 0800 286 331

Other Asia Pacific Countries:

(tel) (65) 6375 8100
(fax) (65) 6755 0042
(e-mail) tm_ap@agilent.com

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2001, 2004
Printed in USA July 14, 2004
5968-8807EN



www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.



Agilent Technologies